

DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011 amended by Commissions delegated Regulation (EU) No 574/2014

No. 153 Unique identification code of the product-type: VANDEX CEMLINE FS GREY							
					Intended use/es:		
						CC fine mortar for non-structural repair (based on hydraulic cement) Applying mortar by hand (3.1) Spraying mortar (3.3)	
Manufacturer:	Vandex Isoliermittel-Gesellschaft m.b.H. Industriestraße 21 DE-21493 Schwarzenbek						
System/s of AVCP:	System 2+						
Harmonised standard:	EN 1504-3:2005						
Notified body/ies:	Material profitantials für das Bauwesen Identification number 0761						



Declared performance/s:

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Compressive strength	class R4 ≥ 45 MPa		
Chloride ion content	≤ 0.05 %		
Adhesive bond	≥ 2,0 MPa		
Carbonation resistance	No performance determined (NPD)		
Modulus of elasticity	≥ 20 GPa		
Thermal compatibility Part 1: Freeze thaw with de-icing salt immersion	≥ 2,0 MPa	System 2+	EN 1504-3:2005
Part 4: Dry thermal cycling	≥ 2,0 MPa		
Capillary absorption	$\leq 0.5 \text{ kg/m}^2 \cdot \text{h}^{0.5}$		
Reaction to fire	class A1		
Dangerous substances	complies with 5.4		

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Schwarzenbek, 10.05.2019

Marc Torben, Managing Director

Edition: May 2019



DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011 amended by Commissions delegated Regulation (EU) No 574/2014

No. 154 Unique identification code of the product-type: VANDEX CEMLINE FS WHITE							
					Intended use/es:		
						CC fine mortar for non-structural repair (based on hydraulic cement) Applying mortar by hand (3.1) Spraying mortar (3.3)	
Manufacturer:	Vandex Isoliermittel-Gesellschaft m.b.H. Industriestraße 21 DE-21493 Schwarzenbek						
System/s of AVCP:	System 2+						
Harmonised standard:	EN 1504-3:2005						
Notified body/ies:	IBMB TO BRAUSCHWEIG						
	Identification number 0761						



Declared performance/s:

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Compressive strength	class R4 ≥ 45 MPa		EN 1504-3:2005
Chloride ion content	≤ 0.05 %	System 2+	
Adhesive bond	≥ 2,0 MPa		
Carbonation resistance	No performance determined (NPD)		
Modulus of elasticity	≥ 20 GPa		
Thermal compatibility Part 1: Freeze thaw with de-icing salt immersion	≥ 2,0 MPa	- Oystem 21	
Capillary absorption	≤ 0.5 kg/m² · h ^{0,5}		
Reaction to fire	class A1		
Dangerous substances	complies with 5.4		

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Schwarzenbek, 10.05.2019

Marc Torben, Managing Director

Edition: May 2019