

## **DECLARATION OF PERFORMANCE**

according to Annex III of the Regulation (EU) No. 305/2011

Name of the product

## **VANDEX CEMELAST WHITE**

No. 267/150

1. Unique identification code of the product-type:

EN 1504-2:ZA.1d,1e

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

batch number: see packaging of the product

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

## Surface protection coating

Protection against ingress (1.3)
Moisture control (2.2)
Increasing resistivity (8.2)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Vandex Isoliermittel-Gesellschaft m.b.H. Industriestraße 19-23 DE-21493 Schwarzenbek

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 2+

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

EN 1504-2, System 2+:

The notified body



Identification number 0761

performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued:

Certificate of conformity of the factory production control 0761-CPR-0110

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

not relevant



## 9. Declared performance

EN 1504-2:ZA,1d,1e
The product VANDEX CEMELAST WHITE consists of the components:
VANDEX CEMELAST WHITE POWDER
VANDEX CEMELAST LIQUID

Essential characteristics	Performance	Harmonised Technical specification
Permeability to CO <sub>2</sub>	s <sub>D</sub> > 50 m	
Water vapour permeability	class II 5 m $\leq$ s <sub>D</sub> $\leq$ 50 m	
Capillary water absorption	$w < 0.1 \text{ kg/m}^2 \cdot \text{h}^{0.5}$	
Crack bridging ability	class A2 (20 ℃)	EN 1504-2:2004
Adhesion strength	≥ 0.8 MPa	
Reaction to fire	class E	
Dangerous substances	complies with 5.3	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Schwarzenbek, 01.07.2013

Christian Biner, Managing Director

Edition: July 2013